

MANUAL AND AUTOMATIC SWING FIRE HOSE REEL

PRODUCT OVERVIEW

ARCHER Fire hose reel is available for manual and automatic swing type complete with stainless automatic stop valve which will fully open within 3 1/2 revolutions of the reel. Hose reel is supplied with a swing arm and mounting which simplifies the installation for left and right direction. Complete with jet/spray nozzle size 25 mm flow rate at 2/6 Bar about 39/68 L /Min certificate by LPCB. ...Hose reel with powder coated and anti-ultraviolet side discs. There can be pressure gauge at the reel axis. applicable for wall mounting or cabinet mounting ; use nipples not hose clamps, to fill in the interface between hose and waterway. Once being screwed tightly,no leakage.

APPLICATION

Suitable for fire fighting use in shopping malls, hotels ,office buildings and industrial areas ,also be used for construction sites, floor cleaning ,car washing ,garden watering etc;

STANDARD APPROVED

The hose reel has been designed and constructed by LPCB to EN671-1:2012

WORKING PRESSURE

Maximum Pressure : 12 Bar
 Test Pressure : 18 Bar
 Burst Pressure : 40 Bar

FIG : CSJR-04-A(B)/ CSJR-04-B(B)
 / CSJR-04-C/CSJR-04-D



CSJR-04-A(B)
 CSJR-04-B(B)



CSJR-04-D



N-11-2



N-09-02

TECHNICAL DATA FIRE HOSE REEL

| PART | MATERIAL | PART | MATERIAL |
|-----------------|-----------------|------------------|------------------------|
| Drum | Steel | Water way | Aluminium alloy |
| Arm | Aluminium alloy | Spring | zinc-plated steel |
| Automatic Valve | brass | Hose | Pvc & Polyester yan |
| Nipple | aluminium | Finishing | RAL3000 powder coating |
| Hub | steel | Jet/Spray nozzle | Brass/nylon |

DESCRIPTION FOR FIRE HOSE REEL

| MODEL NO. | HOSE DIMENSION & LENGTH | HEIGHT (A IN MIN) | WIDTH (B IN MIN) | DEPTH (C IN MIN) | CABINET SIZE (WxHxD)MIN | TYPE |
|--------------|-------------------------|-------------------|------------------|------------------|-------------------------|---------------------|
| CSJR-04-A(B) | 19mm x 30m | 570 | 580 | 300 | 700 x 700 x 330 | MANUAL & AUTOMMATIC |
| CSJR-04-B(B) | 25mm x 30m | 570 | 580 | 300 | 700 x 700 x 330 | MANUAL & AUTOMMATIC |
| CSJR-04-C | 19mm x 36m | 550 | 510 | 320 | 700 x 700 x 350 | MANUAL & SWING PIPE |
| CSJR-04-D | 25mm x 30m | 570 | 580 | 300 | 700 x 700 x 330 | AUTOMATIC SWINTYPE |